

DECLARATION OF PERFORMANCE

No: 0338-CPR-0040-2018

Terram 1C1

Fiberweb Maldon
 Fiberweb Geosynthetics Ltd
 Blackwater Trading Estate
 The Causeway
 Maldon CM9 4GG
 United Kingdom

T: +44 (0)1621 874200
 F: +44 (0)1621 874299

Harmonised technical specification	Intended uses
EN 13252: 2016 Geotextiles for drainage systems	f/f+S/d

Essential characteristics	Performance
Tensile Strength	EN ISO 10319 MD 20.0kN/m (-2.0kN/m) CMD 20.0kN/m (-2.0kN/m)
Tensile Elongation	EN ISO 10319 MD 35% (±15%) CMD 35% (±15%)
Dynamic Perforation	EN ISO 13433 38mm (+5mm)
Resistance to static puncture	EN ISO 12236 3.3kN (-0.33kN)
Opening size	EN ISO 12956 75µm (± 20µm)
Water Permeability	EN ISO 11058 50.10 ⁻³ m/s (-15.10 ⁻³ m/s)
In-plane water flow capacity (soft platens)	EN ISO 12958 85.10 ⁻⁵ m ² /s (-15.10 ⁻⁵ m ² /s)
Dangerous Substances	Less than required by national regulations within EU member states

Note: Testing on Dynamic perforation/Opening Size and Water Permeability is performed on the Geotextile fabric prior to lamination and is based on a single geotextile .

Durability

To be covered within 2 weeks after installation

Predicted to be durable a minimum of 5 years for non-reinforcing applications in natural soils with 4 ≤ pH ≤ 9 and soil temperatures ≤25°C

System: 2+

In case of the declaration of performance concerning a construction product covered by a harmonised standard: Notified factory production control certification body No. 0338 BTTG performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of the factory production control.

Authorised Representative:



Mia Browning—Quality and Compliance Manager